

Technical Specifications

Power supply	via AC unit
Power consumption	typ. 0.2W, max. 0.3W
Loxone Air interface	868MHz (SRD Band Europe), 4 channels, max. 15.1mW e.r.p. 915MHz (ISM Band Region 2), 10 channels, max. 13.2mW internal antenna
Ambient Temperature	-20 ... 65°C / -4 ... 149°F
Humidity	max. 95% r.H. (non condensing)
Degree of protection	IP20

Connecting cable

Wire cross-section	0.14mm ² / AWG26
Temperature resistance	80°C / 176°F
Length	300mm / 11.81"
Part. No.	000584



For more information
about this product, visit
loxone.com/help/AC-Control-Air-100555

An up-to-date List of compatible AC units is available online:
shop.loxone.com/ac-control/

**Loxone
Electronics GmbH**
Smart Home 1
4154 Kollerschlag
Austria

Loxone UK
The Forum
Station Road
Theale, RG7 4RA
United Kingdom



For additional information,
declaration of conformity, visit
www.loxone.com/datasheets

V050623

Need Help?
loxone.com/support



AC Control Air for Mitsubishi Electric

Part No.: 100555

About the Product

With the AC Control Air for Mitsubishi Electric you can integrate Mitsubishi air conditioners easily, quickly and seamlessly into your Loxone installation. Intelligent control of the air conditioners can significantly increase comfort and reduce energy consumption by more than 30% at the same time. This saves costs and protects the planet.

No additional power supply necessary
Simple commissioning via Plug & Play
very compact design: 38.3x34.3x10,5mm
incl. full user interface and control in the Loxone App



Installation may only be carried out with the power supply to the air conditioner switched off!

